




Product Code: EMP.PLS.9LG020

- Lpg or Natural Gas
- Magnet safety valves.
- Specially designed 'V' shaped grill, waste oils go to the discharge at the front.



- Stainless steel all outside body.
- Top plate thickness 2mm body 1mm stainless steel
- Piezoelectric ignition system.
- The protection sheet made of stainless steel prevents oil splashes on the back and sides.
- Dual models, cooking surface temperature is controlled by 2 separate gas valves. So, two different temperatures are provided for the cooking surface temperature.
- The waste oil chamber is located under the combustion section of the device. The waste oil and particles formed are collected in the chamber. Thus, ease of cleaning and maintenance is provided.
- Gas taps with safety devices are used to increase safety and thermocouples for flame monitoring.


800

Front

379

Side 84,5 379 97,9 687,5 143,9 929

763



- G1 Gas Inlet
- G2 Optional Gas Inlet

Installation Information

Total Power	20,60 kW
Gas Consumption NG	2,18 m³/h
Gas Consumption LPG	0,86 kg/h

an opening of 150 mm or heat insulation is required.

Main Information

Length	800 mm	
Depth	930 mm	
Height	316 mm	
Weight	126 kg	
m³	0,28	
Packed Length	890 mm	
Packed Depth	1000 mm	
Packed Height	620 mm	
Packed Weight	140 kg	
m ³	0,55	
If this device is placed near another		
heat-sensitive device or near the furniture;		